



**Providing Stormwater and
Septic Solutions Since 1986**

CULTEC, Inc.
878 Federal Road
P.O. Box 280
Brookfield, CT 06804 USA

Phone: 203.775.4416
Fax: 203.775.1462
Email: custservice@cultec.com
Website: www.cultec.com

MODEL # 410 STORMWATER FILTER FABRIC, CULTEC NO. 410 FILTER FABRIC

A non-woven polypropylene filter fabric that may be used with CULTEC Contactor® and Recharger® stormwater installations. CULTEC Stormwater Systems are typically enveloped top, sides and bottom with filter fabric in order to provide a barrier that prevents soil intrusion into the stone.



[Specifications](#) | [Technical References](#)

Specifications

Appearance	Black
Grab Tensile (ASTM-D-4632)	90 lbs. 400 N
Elongation (ASTM D-4632)	50 %
Trapezoid Tear (ASTM-D-4533)	35 lbs. 155 N
Puncture (ASTM-D-4833)	55 lbs. 245 N
Mullen Burst (ASTM-D-3786)	175 psi 1205 kPa
Apparent Opening Size (ASTM-D-4751)	70 U.S. Sieve 0.21 mm

Permittivity (ASTM-D-4491)	2.0 Sec. -1
Permeability (ASTM D 4491)	0.2 cm/sec
Flow Rate (ASTM-D-4491)	145 gal/min/sf 5908 l/min/sq.mt
UV Resistance (ASTM-D-4355)	70

Technical References

Downloads

[PDF - CULTEC No. 410 Filter Fabric Submittal - Stormwater](#)