



ZOOM OF SIDE PORTAL SHOWING MAX. PIPE O.D.

CULTEC HVLV 180SC CHAMBER STORAGE = 3.445 CF/FT (0.32 m3/m)
 ALL HVLV 180SC UNITS ARE MARKED WITH A COLOR STRIPE FORMED INTO THE PART ALONG THE LENGTH OF THE CHAMBER. MAY BE CAST DIRECTLY INTO A CATCHBASIN. SIDE PORTALS MUST BE TRIMMED ON SITE. SECTIONS TO BE OVERLAPPED ONE RIB ON EACH TO ACHIEVE 58 INCH [1473 mm] CENTER-TO-CENTER SPACING OF PORTALS. SECTIONS TO BE OVERLAPPED TWO RIBS ON EACH END TO ACHIEVE 52 INCH [1321 mm] CENTER-TO-CENTER SPACING OF PORTALS



CULTEC, Inc.

Subsurface Stormwater Management Systems
 P.O. Box 280
 878 Federal Road
 Brookfield, CT 06804
 www.cultec.com
 PH: (203) 775-4416
 PH: (800) 4-CULTEC
 FX: (203) 775-1462
 tech@cultec.com

THIS DRAWING WAS PREPARED TO SUPPORT THE DESIGN ENGINEER FOR THE PROPOSED SYSTEM. IT IS THE ULTIMATE RESPONSIBILITY OF THE DESIGN ENGINEER TO ASSURE THAT THE STORMWATER SYSTEM'S DESIGN IS IN FULL COMPLIANCE WITH ALL APPLICABLE LAWS AND REGULATIONS. IT IS THE DESIGN ENGINEER'S RESPONSIBILITY TO ENSURE THAT THE CULTEC PRODUCTS ARE DESIGNED IN ACCORDANCE WITH CULTEC'S MINIMUM REQUIREMENTS. CULTEC INC. DOES NOT APPROVE PLANS, SIZING, OR SYSTEM DESIGNS. THE DESIGNING ENGINEER IS RESPONSIBLE FOR ALL DESIGN DECISIONS.

HVLV 180BSC STRAIGHT CONNECTOR 3 VIEW

HVLV 180SC STRAIGHT CONNECTOR 3 VIEW

PROJECT NO:	DATE: 09/18/14
DESIGNED BY: TECH.	DRAWN BY: TECH
SCALE: N.T.S.	SHEET NO: 1 OF 1